

STPT370-SH
(高温配管用炭素鋼鋼管)

KSTPT38-SH
(船級協会規格)

STS370-SH
(高圧配管用炭素鋼鋼管)

A呼称	S/40		S/80		S/160		摘要
	外径	肉厚	肉厚		肉厚		
	10.5	1.7	2.4				
6A		*	*				SC
	13.8	2.2	3.0				
8A		*	*				SC
	17.3	2.3	3.2				
10A		*	*				SC
	21.7	2.8	3.7		4.7		
15A		*	*		*		SC
	27.2	2.9	3.9		5.5		
20A					*		
	34.0	3.4	4.5		6.4		
25A							
	42.7	3.6	4.9		6.4		
32A							
	48.6	3.7	5.1		7.1		
40A							
	60.5	3.9	5.5		8.7		
50A							
	76.3	5.2	7.0		9.5		
65A							
	89.1	5.5	7.6		11.1		
80A							
	101.6	5.7	8.1		12.7		
90A							
	114.3	6.0	8.6		13.5		
100A							
	139.8	6.6	9.5		15.9		
125A							
	165.2	7.1	11.0		18.2		
150A							
	216.3	8.2	12.7		23.0		
200A							
	267.4	9.3	15.1		28.6		
250A							
	318.5	10.3	17.4		33.3		
300A							
	355.6	11.1	19.0		35.7		
350A							
	406.4	12.7	21.4		40.5		
400A							

すべて定尺:5500mmです

***印のみの在庫となり他は取扱品となります**

KSTPT38-SHはすべて取扱品です